

Data Sheet - Kodicom KSR-304N

4 Channel LCD-DVR combo



the home of
Kodicom in
the UK

Main features

- High Quality Picture Resolution
- Multi-Function Monitoring
- Intuitive GUI Operation
- Easy Picture Retrieval
- Compact Picture Storage (MPEG4)
- Event Controlled Recording options
- Remote Observation Through Network CMS
- Stylish design
- Multiple User Levels
- Watermark Function
- 2-way Audio
- Remote Upgrade and Programming Options
- Multilingual



Ideal Applications

- Small – Medium commercial surveillance
- Schools
- Department Stores
- Convenience Stores
- Exhibition Halls
- Jewellers
- Galleries and Museums
- Farms
- Public Houses
- Restaurants
- Banks

The **Kodicom KSR-304N** is the benchmark for all Standalone platform DVR's. This well established, ultra stable product is a must for any serious surveillance system. Rammed with the latest features there are many ways this DVR out performs its standalone counterparts.

Picture retrieval couldn't be easier through the units intuitive playback screen, searching by time, date or alarm event. The picture quality needs to be seen to be believed eclipsing most of the other machines claiming similar specifications with its crisp clear images, this Kodicom machine is clearly best in class by many measures.

The unit comes added features such as audio Recording and is network ready, the viewing software reduces the need to have standalone monitors, programmable spot monitor outputs are also available (model specific).

Remote view and alarms can be seen via the CMS software also enabling PTZ control, remote software upgrade, 2 way audio, as well as remote programming.

The **KSR-304N** represents the must have for any serious surveillance application where reliability and picture quality are the main considerations.



Data Sheet - Kodicom KSR-304N

Easy to use 4 Channel DVR



the home of
Kodicom in
the UK

Specifications (all specs subject to modification)

Model		KSR-304N
Display	Speed	NTSC : 120 fps PAL : 100 fps
	Screen Division	x 1 and x 4 Division
Recording	Max Speed (@CIF)	NTSC : 120 fps PAL : 100 fps
Video	Resolution	NTSC : 740 x 480, 704 x 240, 352 x 240
		PAL : 704 x 576, 704 x 288, 352 x 288
	Recording Option	Continuous, Motion, Sensor and Pre-Alarm
	Format	NTSC / PAL
	CODEC	MPEG4
	Input	4 Channel
	Output	7" Wide LCD (800 x 480), CVBS 1 Port (Quad)
Audio	Input	1 Channel (Line input)
	Output	1 Channel
	CODEC	ADPCM
Alarm	Input	2 Ports
	Output	2 Ports
Network	Transmission	Ethernet (RJ45)
	Protocol	TCP/IP (Support Dynamic IP)
Backup	Device	USB, Network Device
Other Functions	Remote Control	Remote Software (CMS)
	Remote Alarm	E-mail, CMS report
	PTZ	RS232C, RS485
	W/D Function	Yes
	Image Authentication	Watermark
	Language	10 Languages
	Password	Multi-Level User Password Authorization
	USB	1 Port (USB 2.0)
Working Temperature		0°C - 40°C
Power Source		100 -240 Vac 50/60Hz 12V Adaptor included)
Dimensions		185mm(W) x 60mm(H) x 265mm(D) 1.5Kg (5.94lbs)

www.CctvX-cctv.com

Contact us @

cctvX
Unit 7 Cygnet Business Centre
Hanley Swan
Worc.
WR8 0EA

Tel: +44 1684 311885
Fax: +44 1684 311912
sales@cctvX-cctv.com
www.cctvX-cctv.com

Part of the new solutions range of publications from cctvX, the specialist distributor in CCTV products
cctvX the exclusive home of the World leading Kodicom range of Surveillance products including DVR's and Cameras