

## High Resolution IR Dome Camera d144cb550IR



### Key Features

- 1/3" SONY SUPER HAD II CCD
- High Resolution: 540TVL
- Day & Night with removable IR-cut filter (Optional)
- Min. illumination: 0.08Lux/F1.20Lux(IR LED On)
- Automatic back-light compensation improves the image Quality
- Auto White Balance (AWB), AGC
- AC24V
- 3-Axis



### Specifications

Model	SN-FXP0580DIR
Signal System	PAL/NTSC
Scanning Mode	2:1 Interface
Image Sensor	1/3" SONY SUPER HAD II CCD
Sync. System	Internal
Effective Pixel Number	NTSC: 768(H) x 494 (V) PAL: 752(H) x 582 (V)
Horizontal Resolution	540TVL
Video Output Level	1.0Vp-p (75Ω, Composite)
S/N Ratio	More than 50dB (AGC Off)
Lens	Vari-focal Lens, 4.9mm (optional)
Min. Illumination	0.08Lux/F1.2 0Lux(LED ON)
Electronic Shutter Speed	NTSC: 1/60 ~ 1/100,000 sec PAL: 1/50 ~ 1/100,000 sec
White Balance	Auto
BLC	Auto
AGC	Auto
IR LED Drive	850nm
IR LED Lighting Distance	Max 10-15m
IR -LED	21PCS
Consumed Current	300mA (LED ON)
Supplied Voltage	DC12V/AC24V (Optional)
Dimension	φ 150X127mm
Weight	950g
Operation Temperature	-10°C ~ +50°C, RH 95% Max

### Dimension ( unit: mm )

