

# IR Night Vision Camera

## Vandalproof IR Dome Camera

### KD-3050IR

#### Key Features

- TDN, Min. Illumination: 0 Lux (IR LED ON)
- Built-in IR LED
- Auto White Balance (AWB), AGC, BLC
- Anti-flare Double Glass
- Vandal-Resistant Housing
- Manual Pan & Tilt for easy installation
- Supplied Voltage: DC 12V
- Night View Distance Up To 10-15m



#### Dimension (unit: mm)



#### Specifications

Model	KD3050IR
Signal System	PAL/NTSC
Image Sensor	1/3"SONY CCD
Sync. Mode	Internal
Effective Pixel Number	NTSC: 510(H) x 494 (V) PAL: 500(H) x 582 (V)
Horizontal Resolution	420 TVL
Video Output Level	1.0Vp-p (75 Ω, Composite)
S/N Ratio	More than 48dB
Lens	detailed for order guidance
Min. Illumination	0.3Lux/F1.2 0Lux(LED ON)
Electronic Shutter Speed	NTSC: 1/60 ~ 1 /100,000 secretary, PAL: 1/50 ~ 1 /100,000 sec
White Balance	Auto
BLC	Auto
AGC	Auto
IR-LED Wavelength	Wave Length: 850nm
Consumed Current	120mA(IROFF)+ 300mA(IRON)
Supplied Voltage	DC 12V
Dimension	∅ 94 × 80mm
Weight	Approx. 400g
IR LED Lighting Distance	10~ 15m